

1 Identification

- **Product identifier**
- **Trade name:** 39728 Super SEM Flex
- **Article number:** 39728
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
SEM Products Inc.
1685 Overview Drive
Rock Hill, SC 29730
803 207 8225
- **Information department:**
cust_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

toluene

butanone

n-butyl acetate

Trade name: 39728 Super SEM Flex

(Contd. of page 1)

· **Hazard statements**

- H225 Highly flammable liquid and vapor.
- H319 Causes serious eye irritation.
- H361 Suspected of damaging fertility or the unborn child.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Precautionary statements**

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- P240 Ground/bond container and receiving equipment.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P260 Do not breathe dust/fume/gas/mist/vapors/spray.
- P264 Wash thoroughly after handling.
- P271 Use only outdoors or in a well-ventilated area.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P314 Get medical advice/attention if you feel unwell.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P403+P235 Store in a well-ventilated place. Keep cool.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**



· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.



Trade name: 39728 Super SEM Flex

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**
Mixture: consisting of the following components.
Weight percentages

- **Dangerous components:**

| | | |
|----------|---------------------------------|---------|
| 78-93-3 | butanone | 13-30% |
| 108-88-3 | toluene | ≥7-<10% |
| 123-86-4 | n-butyl acetate | ≥7-<10% |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 1.5-5% |

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)



Trade name: 39728 Super SEM Flex

(Contd. of page 3)

- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

| · PAC-1: | | |
|----------|---------------------------------|-----------|
| 78-93-3 | butanone | 200 ppm |
| 108-88-3 | toluene | 67 ppm |
| 123-86-4 | n-butyl acetate | 5 ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 50 ppm |
| · PAC-2: | | |
| 78-93-3 | butanone | 2700* ppm |
| 108-88-3 | toluene | 560 ppm |
| 123-86-4 | n-butyl acetate | 200 ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 1,000 ppm |
| · PAC-3: | | |
| 78-93-3 | butanone | 4000* ppm |
| 108-88-3 | toluene | 3700* ppm |
| 123-86-4 | n-butyl acetate | 3000* ppm |
| 108-65-6 | 2-methoxy-1-methylethyl acetate | 5000* ppm |

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
No special measures required.
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)



Trade name: 39728 Super SEM Flex

(Contd. of page 4)

· Control parameters

· Components with limit values that require monitoring at the workplace:

78-93-3 butanone

| | |
|-----|--|
| PEL | Long-term value: 590 mg/m ³ , 200 ppm |
| REL | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm |
| TLV | Short-term value: 885 mg/m ³ , 300 ppm Long-term value: 590 mg/m ³ , 200 ppm BEI |

108-88-3 toluene

| | |
|-----|---|
| PEL | Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift |
| REL | Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm |
| TLV | Long-term value: 75 mg/m ³ , 20 ppm BEI |

123-86-4 n-butyl acetate

| | |
|-----|---|
| PEL | Long-term value: 710 mg/m ³ , 150 ppm |
| REL | Short-term value: 950 mg/m ³ , 200 ppm Long-term value: 710 mg/m ³ , 150 ppm |
| TLV | Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm |

108-65-6 2-methoxy-1-methylethyl acetate

| | |
|------|-------------------------|
| WEEL | Long-term value: 50 ppm |
|------|-------------------------|

· Ingredients with biological limit values:

78-93-3 butanone

| | |
|-----|---|
| BEI | 2 mg/L Medium: urine Time: end of shift Parameter: MEK |
|-----|---|

108-88-3 toluene

| | |
|-----|--|
| BEI | 0.02 mg/L Medium: blood Time: prior to last shift of workweek Parameter: Toluene |
| | 0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene |
| | 0.3 mg/g creatinine Medium: urine Time: end of shift Parameter: o-Cresol with hydrolysis (background) |

(Contd. on page 6)



Trade name: 39728 Super SEM Flex

(Contd. of page 5)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: According to product specification

· **Odor:** Characteristic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 79-80.5 °C

(Contd. on page 7)



Trade name: 39728 Super SEM Flex

(Contd. of page 6)

| | |
|---|--|
| · Flash point: | -4 °C |
| · Flammability (solid, gaseous): | Not applicable. |
| · Ignition temperature: | 370 °C |
| · Decomposition temperature: | Not determined. |
| · Auto igniting: | Product is not selfigniting. |
| · Danger of explosion: | In use, may form flammable/explosive vapour-air mixture. |
| · Explosion limits: | |
| Lower: | 0,4 Vol % |
| Upper: | 13 Vol % |
| · Vapor pressure at 20 °C: | 233 hPa |
| · Density at 20 °C: | 0.99852 g/cm ³ |
| · Relative density | Not determined. |
| · Vapor density | Not determined. |
| · Evaporation rate | Not determined. |
| · Solubility in / Miscibility with Water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 41.8 % |
| VOC content: | 41.82 % |
| | 417.5 g/l / 3.48 lb/gal |
| · Solids content: | 58.2 % |
| · Other information | No further relevant information available. |

* 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

USA

(Contd. on page 8)



Trade name: 39728 Super SEM Flex

(Contd. of page 7)

11 Toxicological information

- Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

108-88-3 toluene

| | | |
|------------|----------|-----------------------|
| Oral | LD50 | 5,000 mg/kg (rat) |
| Dermal | LD50 | 12,124 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 5,320 mg/l (mouse) |

- Primary irritant effect:
 - on the skin: No irritant effect.
 - on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

| | |
|------------------|---|
| 108-88-3 toluene | 3 |
|------------------|---|

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability: No further relevant information available.
- Behavior in environmental systems:
- Bioaccumulative potential: No further relevant information available.
- Mobility in soil: No further relevant information available.
- Additional ecological information:
- General notes:
 - Water hazard class 2 (Self-assessment): hazardous for water
 - Do not allow product to reach ground water, water course or sewage system.
 - Danger to drinking water if even small quantities leak into the ground.
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- Other adverse effects: No further relevant information available.

USA

(Contd. on page 9)



Trade name: 39728 Super SEM Flex

(Contd. of page 8)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** 1263 Paint, special provision 640D
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR, IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** II
- **Environmental hazards:**
- **Marine pollutant:** Yes
- **Special precautions for user** Warning: Flammable liquids
- **EMS Number:** F-E,S-E
- **Stowage Category** B
- **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

(Contd. on page 10)



Trade name: 39728 Super SEM Flex

(Contd. of page 9)

· **Transport/Additional information:**· **DOT**· **Quantity limitations**

On passenger aircraft/rail: 5 L

On cargo aircraft only: 60 L

· **ADR**· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **IMDG**· **Limited quantities (LQ)**

5L

· **Excepted quantities (EQ)**

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":**

UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II

* **15 Regulatory information**· **Safety, health and environmental regulations/legislation specific for the substance or mixture**· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

78-93-3 butanone

108-88-3 toluene

· **TSCA (Toxic Substances Control Act):**

16883-83-3 benzyl 3-isobutryloxy-1-isopropyl-2-2-dimethylpropyl phthalate

78-93-3 butanone

108-88-3 toluene

123-86-4 n-butyl acetate

108-65-6 2-methoxy-1-methylethyl acetate

· **Proposition 65**· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

· **Carcinogeny categories**· **EPA (Environmental Protection Agency)**

78-93-3 butanone

I

(Contd. on page 11)

USA



Trade name: 39728 Super SEM Flex

(Contd. of page 10)

108-88-3 toluene

II

· TLV (Threshold Limit Value established by ACGIH)

108-88-3 toluene

A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms



GHS02

GHS07

GHS08

· Signal word Danger

· Hazard-determining components of labeling:

toluene

butanone

n-butyl acetate

· Hazard statements

H225 Highly flammable liquid and vapor.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

(Contd. on page 12)



Trade name: 39728 Super SEM Flex

(Contd. of page 11)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Rita Joiner (rjoiner@semproducts.com)

· **Date of preparation / last revision** 11/05/2018 / 14

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

· *** Data compared to the previous version altered.**