


### DESCRIPTION:

PC-3980 quick drier is specially designed for Perfecoat 2K topcoat and Clearcoat. It can speed up the dust free time and air drying time of paint film. It is suitable for spot repair or application at low temperature.

### COMPONENTS:

PC-3980    Quick Drier

### MIX RATIO:



50° F to 59° F: 5-6 gram PC-3980 per RTS 1 quart

32° F to 50° F: 6-10 gram PC-3980 per RTS 1 quart

Below 32° F: 10-15 gram PC-3980 per RTS 1 quart

### Note:

- 1.Pot life of paint mixed with PC-3980 quick drier would be shortened considerably, use up as soon as possible.
- 2.Not recommended addition of PC-3980 quick drier is over 15 gram per RTS 1 quart, otherwise, it would cause paint film embrittlement and loss of gloss .
- 3.PC-3980 quick drier cannot be used as activator, but can be used with activator.
- 4.Shelf Life: 2 years in original sealed can at cool and dry place at 41-95°F.

### PHYSICAL DATA:

VOC: 7.3 lbs/gal

### FOR PROFESSIONAL USE ONLY

Read MSDS Before Use

**NOTE:** The information in this data sheet is based on our knowledge and the current laws. It is always the responsibility of the user to fulfill the requirements of local rules and legislations. The uncertain factors may affect the application of products, such as the condition of substrate. We do not accept any liability on loss, damage and performance of products unless we issue a special agreement. Always read the latest Material Data Sheet and the Technical Data sheet before applying the products.