

## 1 Identification

- **Product identifier**
- **Trade name:** 61033 Multimax Gloss Black
- **Article number:** 61033
- **Application of the substance / the mixture** Coating
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225
- **Information department:**  
cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT
- **Emergency telephone number:** CHEMTREC 1-800-424-9300

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 GHS04 Flame, Gas cylinder

Flam. Aerosol 1 H222

Extremely flammable aerosol.



GHS04 Gas cylinder

Press. Gas

H280

Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Muta. 1B

H340

May cause genetic defects.

Carc. 1B

H350

May cause cancer.

Repr. 2

H361

Suspected of damaging fertility or the unborn child.

STOT RE 1

H372-H373

Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.

Asp. Tox. 1

H304

May be fatal if swallowed and enters airways.



GHS07

Eye Irrit. 2A

H319

Causes serious eye irritation.

STOT SE 3

H336

May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Trade name: 61033 Multimax Gloss Black

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.  
acetone

Solvent naphtha (petroleum), medium aliph.  
Ligroine

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H372-H373 Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P331 Do NOT induce vomiting.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Trade name: 61033 Multimax Gloss Black

(Contd. of page 2)

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = *2
FIRE	4	Fire = 4
REACTIVITY	3	Reactivity = 3

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:**  
Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

67-64-1	acetone	30-40%
68476-86-8	Petroleum gases, liquefied, sweetened	13-30%
78-93-3	butanone	10-13%
64742-89-8	Solvent naphtha (petroleum), light aliph.	5-7%
64742-88-7	Solvent naphtha (petroleum), medium aliph.	5-7%
8032-32-4	Ligroine	1.5-5%
763-69-9	ethyl 3-ethoxypropionate	1-1.5%
108-88-3	toluene	1-1.5%
8052-41-3	Stoddard solvent	≥0.1-≤1%
100-41-4	ethylbenzene	≥0.1-≤1%

### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)



Trade name: 61033 Multimax Gloss Black

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

67-64-1	acetone	200 ppm
78-93-3	butanone	200 ppm
763-69-9	ethyl 3-ethoxypropionate	1.6 ppm
108-88-3	toluene	67 ppm
1330-20-7	xylene	130 ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	18 mg/m <sup>3</sup>
1333-86-4	Carbon black	9 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	300 mg/m <sup>3</sup>
100-41-4	ethylbenzene	33 ppm

### · PAC-2:

67-64-1	acetone	3200* ppm
78-93-3	butanone	2700* ppm
763-69-9	ethyl 3-ethoxypropionate	18 ppm
108-88-3	toluene	560 ppm
1330-20-7	xylene	920* ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	200 mg/m <sup>3</sup>
1333-86-4	Carbon black	99 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	1,800 mg/m <sup>3</sup>
100-41-4	ethylbenzene	1100* ppm

(Contd. on page 5)



Trade name: 61033 Multimax Gloss Black

(Contd. of page 4)

· PAC-3:		
67-64-1	acetone	5700* ppm
78-93-3	butanone	4000* ppm
763-69-9	ethyl 3-ethoxypropionate	110 ppm
108-88-3	toluene	3700* ppm
1330-20-7	xylene	2500* ppm
112926-00-8	precipitated Silica (Silica-Amorphous)	1,200 mg/m <sup>3</sup>
1333-86-4	Carbon black	590 mg/m <sup>3</sup>
8052-41-3	Stoddard solvent	29500** mg/m <sup>3</sup>
100-41-4	ethylbenzene	1800* ppm

## 7 Handling and storage

### · Handling:

#### · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

#### · Information about protection against explosions and fires:

Do not spray on a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

#### · Conditions for safe storage, including any incompatibilities

#### · Storage:

#### · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurized containers.

#### · Information about storage in one common storage facility: Not required.

#### · Further information about storage conditions: Keep receptacle tightly sealed.

#### · Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

#### · Additional information about design of technical systems: No further data; see item 7.

#### · Control parameters

#### · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

#### 67-64-1 acetone

PEL Long-term value: 2400 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm

TLV Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm

Long-term value: 594 mg/m<sup>3</sup>, 250 ppm

BEI

(Contd. on page 6)

USA



**Trade name: 61033 Multimax Gloss Black**

(Contd. of page 5)

**78-93-3 butanone**

PEL Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
 REL Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
 Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
 TLV Short-term value: 885 mg/m<sup>3</sup>, 300 ppm  
 Long-term value: 590 mg/m<sup>3</sup>, 200 ppm  
 BEI

**8032-32-4 Ligroine**

REL Long-term value: 350 mg/m<sup>3</sup>  
 Ceiling limit value: 1800\* mg/m<sup>3</sup>  
 \*15-min  
 TLV TLV Withdrawn - refer to Appendix H

**108-88-3 toluene**

PEL Long-term value: 200 ppm  
 Ceiling limit value: 300; 500\* ppm  
 \*10-min peak per 8-hr shift  
 REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm  
 Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
 TLV Long-term value: 75 mg/m<sup>3</sup>, 20 ppm  
 BEI

**8052-41-3 Stoddard solvent**

PEL Long-term value: 2900 mg/m<sup>3</sup>, 500 ppm  
 REL Long-term value: 350 mg/m<sup>3</sup>  
 Ceiling limit value: 1800\* mg/m<sup>3</sup>  
 \*15-min  
 TLV Long-term value: 525 mg/m<sup>3</sup>, 100 ppm

**100-41-4 ethylbenzene**

PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
 REL Short-term value: 545 mg/m<sup>3</sup>, 125 ppm  
 Long-term value: 435 mg/m<sup>3</sup>, 100 ppm  
 TLV Long-term value: 87 mg/m<sup>3</sup>, 20 ppm  
 BEI

**· Ingredients with biological limit values:**

**67-64-1 acetone**

BEI 50 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

**78-93-3 butanone**

BEI 2 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: MEK

(Contd. on page 7)

Trade name: 61033 Multimax Gloss Black

(Contd. of page 6)

**108-88-3 toluene**

BEI 0.02 mg/L  
Medium: blood  
Time: prior to last shift of workweek  
Parameter: Toluene

0.03 mg/L  
Medium: urine  
Time: end of shift  
Parameter: Toluene

0.3 mg/g creatinine  
Medium: urine  
Time: end of shift  
Parameter: o-Cresol with hydrolysis (background)

**100-41-4 ethylbenzene**

BEI 0.7 g/g creatinine  
Medium: urine  
Time: end of shift at end of workweek  
Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)

-  
Medium: end-exhaled air  
Time: not critical  
Parameter: Ethyl benzene (semi-quantitative)

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.
- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 8)

Trade name: 61033 Multimax Gloss Black

(Contd. of page 7)

- **Penetration time of glove material**  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**  
Safety glasses



Tightly sealed goggles

## 9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**
  - **Form:** Aerosol
  - **Color:** According to product specification
- **Odor:** Characteristic
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**
  - **Melting point/Melting range:** Undetermined.
  - **Boiling point/Boiling range:** 55 °C
- **Flash point:** -103 °C
- **Flammability (solid, gaseous):** Not applicable.
- **Ignition temperature:** 265 °C
- **Decomposition temperature:** Not determined.
- **Auto igniting:** Product is not selfigniting.
- **Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.
- **Explosion limits:**
  - **Lower:** 1.8 Vol %
  - **Upper:** 13 Vol %
- **Vapor pressure at 20 °C:** 233 hPa
- **Density at 20 °C:** 0.7121 g/cm<sup>3</sup>
- **Relative density** Not determined.
- **Vapor density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with**
  - **Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - **Dynamic:** Not determined.
  - **Kinematic:** Not determined.

(Contd. on page 9)





Trade name: 61033 Multimax Gloss Black

(Contd. of page 8)

· <b>Solvent content:</b>	
<b>Organic solvents:</b>	89.8 %
<b>VOC content:</b>	58.35 %
	579.8 g/l / 4.84 lb/gl
· <b>Solids content:</b> 10.2 %	
· <b>Other information</b> No further relevant information available.	

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**  
**64742-88-7 Solvent naphtha (petroleum), medium aliph.**

Oral	LD50	>6,500 mg/kg (rat)
Dermal	LD50	>3,000 mg/kg (rab)
Inhalative	LC50/4 h	>14 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
The product can cause inheritable damage.

· **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

108-88-3	toluene	3
1330-20-7	xylene	3
1333-86-4	Carbon black	2B
	BENTONITE	suspected carcinogen <2% 14808-60-7
100-41-4	ethylbenzene	2B

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

(Contd. on page 10)

Trade name: 61033 Multimax Gloss Black

(Contd. of page 9)

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

**12 Ecological information**

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

**13 Disposal considerations**

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

**14 Transport information**

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1950
- **UN proper shipping name**
- **DOT** Aerosols, flammable
- **ADR** 1950 Aerosols
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable

· **Transport hazard class(es)**

· **DOT**





· **Class**

2.1

(Contd. on page 11)

Trade name: 61033 Multimax Gloss Black

(Contd. of page 10)

· <b>Label</b>	2.1
· <b>ADR</b>	
	
· <b>Class</b>	2 5F Gases
· <b>Label</b>	2.1
· <b>IMDG, IATA</b>	
	
· <b>Class</b>	2.1
· <b>Label</b>	2.1
· <b>Packing group</b>	
· <b>DOT, ADR, IMDG, IATA</b>	Void
· <b>Environmental hazards:</b>	
· <b>Marine pollutant:</b>	No
· <b>Special precautions for user</b>	Warning: Gases
· <b>EMS Number:</b>	F-D,S-U
· <b>Stowage Code</b>	SW1 Protected from sources of heat. SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· <b>Segregation Code</b>	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	1L
· <b>Excepted quantities (EQ)</b>	Code: E0 Not permitted as Excepted Quantity

(Contd. on page 12)



Trade name: 61033 Multimax Gloss Black

(Contd. of page 11)

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

78-93-3	butanone
108-88-3	toluene
1330-20-7	xylene
100-41-4	ethylbenzene

· TSCA (Toxic Substances Control Act):

67-64-1	acetone
78-93-3	butanone
64742-89-8	Solvent naphtha (petroleum), light aliph.
64742-88-7	Solvent naphtha (petroleum), medium aliph.
8032-32-4	Ligroine
763-69-9	ethyl 3-ethoxypropionate
108-88-3	toluene
1330-20-7	xylene
1333-86-4	Carbon black
8052-41-3	Stoddard solvent
100-41-4	ethylbenzene

· TSCA new (21st Century Act) (Substances not listed)

68476-86-8	Petroleum gases, liquefied, sweetened
------------	---------------------------------------

· Proposition 65

· Chemicals known to cause cancer:

1330-20-7	xylene
1333-86-4	Carbon black
100-41-4	ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

108-88-3	toluene
----------	---------

· Cancerogenity categories

· EPA (Environmental Protection Agency)

67-64-1	acetone	I
---------	---------	---

(Contd. on page 13)

Trade name: 61033 Multimax Gloss Black

(Contd. of page 12)

78-93-3	butanone	I
108-88-3	toluene	II
1330-20-7	xylene	I
100-41-4	ethylbenzene	D

· **TLV (Threshold Limit Value established by ACGIH)**

67-64-1	acetone	A4
8032-32-4	Ligroine	A3
108-88-3	toluene	A4
1330-20-7	xylene	A4
1333-86-4	Carbon black	A4
100-41-4	ethylbenzene	A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS04 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.  
acetone

Solvent naphtha (petroleum), medium aliph.  
Ligroine

· **Hazard statements**

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H319 Causes serious eye irritation.

H340 May cause genetic defects.

H350 May cause cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H372-H373 Causes damage to organs through prolonged or repeated exposure. May cause damage to the central nervous system through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Pressurized container: Do not pierce or burn, even after use.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

(Contd. on page 14)


**Trade name: 61033 Multimax Gloss Black**

(Contd. of page 13)

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P331	Do NOT induce vomiting.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P314	Get medical advice/attention if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P410+P403	Protect from sunlight. Store in a well-ventilated place.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** Rita Joiner (rjoiner@semproducts.com)

- **Date of preparation / last revision** 03/14/2018 / 13

- **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

(Contd. on page 15)



Printing date 03/14/2018

Reviewed on 06/28/2017

**Trade name: 61033 Multimax Gloss Black**

(Contd. of page 14)

REL: Recommended Exposure Limit  
BEI: Biological Exposure Limit  
Flam. Aerosol 1: Aerosols – Category 1  
Press. Gas: Gases under pressure – Compressed gas  
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A  
Muta. 1B: Germ cell mutagenicity – Category 1B  
Carc. 1B: Carcinogenicity – Category 1B  
Repr. 2: Reproductive toxicity – Category 2  
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3  
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1  
Asp. Tox. 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**

USA