



GENERAL INFORMATION

PRONTO™ Kombi Spot Putty is a single component, ultra smooth and fast drying putty that is ideal for use on small, last minute repairs. This ready to use putty is formulated for excellent adhesion to properly prepared metal, galvanized, aluminum, primers and existing finishes.



1. PART NUMBER

- 32046 PRONTO™ - 5 oz. tube

2. PRODUCT USES

- Ideal for last minute repairs, minor imperfections, pinholes, surface flaws and scratch marks in body repair work.



3. MIXING

- Ready to use



4. SURFACE PREPARATION

- Clean surface of all contaminants with wax & grease remover such as 1240-1. Sand surface. Clean with wax & grease remover. Dry thoroughly.



5. APPLICATION

- 1 – 3 thin coats, allowing 15 minutes in between coats (@ 72° F / 22° C).
Note: Avoid excessive film build.



6. SUBSTRATES

- Metal
- Aluminum
- Galvanized and other zinc-coated steel
- 1K and 2K Primers
- Aged, sanded OEM Topcoats

7. FINISHING

Dry Time:
20 minutes (@ 72° F / 22° C)
10 minutes (@ 100°F / 40°C)

8. TOPCOATING

- May be topcoated with primer, primer surfacer, sealer, basecoat and single stage refinish coatings.



9. TECHNICAL INFORMATION

Appearance as Packaged	Olive Drab	
Mix Ratio	Ready to Use	
VOC	Packaged	396 g/l
	Applied	3.31 g/l
Solids	75.3%	
Pot Life	Tack free time 45 – 90 seconds (depending upon thickness & temperature)	



10. HEALTH & SAFETY

- Read all warnings, first aid, and safety for all components before using. Keep out of reach of children and animals. Protect hands with impervious rubber gloves. Wear face, skin, and eye protection. When sanding, we recommend the use of a respiratory covering device to protect from dust (MSA mask P/N 459029 with MSA cartridge 464029 or equivalent). When using power equipment, refer to power tool manufacturer's recommendations for safety equipment. USC products are for industrial use by trained professionals only.

- Emergency Medical or Spill Control Information:
In U.S. and Canada call CHEMTREC at 1-800-424-9300