

Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

1. Identification

1.1. Product Name: Urethane Windshield Adhesive

Product Number: 4502

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use For Professional and Industrial Use Only. Not for sale to the general public.
One component adhesive for automotive industry.

Identified Uses	Industrial	Professional
SEALANTS AND ADHESIVES FORMULATIONS IN INDUSTRY	✓	-
INDUSTRIAL APPLICATIONS OF SEALANTS AND ADHESIVES	✓	✓
CHEMICAL SUBSTANCE USE IN LABORATORY, INDUSTRIAL	✓	-

1.3. Details of the supplier of the SDS

SUPPLIER: Transtar Autobody Technologies

ADDRESS: 2040 Heiserman dr., Brighton, Mi. 48114

Telephone: 810-360-1600

1.4. 24 Hour Emergency telephone number

USA & Canada: (Chemtrec) 800-424-9300

International: (Chemtrec) +1-703-741-5970

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Carcinogenicity, category 2

Respiratory sensitization, category 1

Skin sensitization, category 1

Suspected of causing cancer.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Hazard pictograms:



Signal words: Danger

Hazard statements:

H351 Suspected of causing cancer.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

Precautionary statements:

4502

2. Hazards identification ... / >>

Prevention:

- P261** Avoid breathing dust / fume / gas / mist / vapours / spray.
P202 Do not handle until all safety precautions have been read and understood.
P201 Obtain special instructions before use.
P280 Wear protective gloves/ protective clothing / eye protection / face protection.
P272 Contaminated work clothing should not be allowed out of the workplace.
P284 [In case of inadequate ventilation] wear respiratory protection.

Response:

- P308+P313** IF exposed or concerned: Get medical advice / attention.
P342+P311 If experiencing respiratory symptoms: call a POISON CENTER / doctor / . . .
P333+P313 If skin irritation or rash occurs: Get medical advice / attention.
P304+P340 IF INHALED: remove person to fresh air and keep comfortable for breathing.
P302+P352 IF ON SKIN: wash with plenty of water / . . .
P363 Wash contaminated clothing before reuse.

Storage:

- P405** Store locked up.

Disposal:

- P501** Dispose of contents / container according to local regulation.

2.2. Other hazards

Information not available

3. Composition/information on ingredients**3.2. Mixtures**

Contains:

Identification

x = Conc. %

Classification:

DIISONONYL PHTHALATE

CAS 28553-12-0 28 ≤ x < 32

EC 249-079-5

INDEX

CARBON BLACK.

CAS 1333-86-4 28 ≤ x < 32

EC 215-609-9

INDEX

DIPHENYLMETHANE-4,4'-DIISOCYANATE

CAS 101-68-8 0.7 ≤ x < 1

**Carcinogenicity, category 2 H351, Acute toxicity, category 4 H332,
 Specific target organ toxicity - repeated exposure, category 2 H373, Eye irritation,
 category 2 H319, Skin irritation, category 2 H315,
 Specific target organ toxicity - single exposure, category 3 H335,
 Respiratory sensitization, category 1 H334, Skin sensitization, category 1 H317**

EC 202-966-0

INDEX 615-005-00-9

* There is a batch to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures**4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

4502

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

USA	NIOSH-REL	NIOSH publication No. 2005-149, 3th printing, 2007.
USA	OSHA-PEL	Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.
USA	CAL/OSHA-PEL	California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs).
	TLV-ACGIH	ACGIH 2020

CARBON BLACK.

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
CAL/OSHA-PEL	USA	3.5				
OSHA-PEL	USA	3.5				
OSHA	USA	3.5				
CAL/OSHA	USA	3.5				
NIOSH	USA	3.5				

DIPHENYLMETHANE-4,4'-DIISOCYANATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m ³	ppm	mg/m ³	ppm	
TLV-ACGIH	-	0.051	0.005			
OSHA	USA			0.2 (C)	0.02 (C)	
CAL/OSHA	USA	0.051	0.005			
NIOSH	USA	0.05	0.005	0.2 (C)	0.02 (C)	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
------------	-------	-------------

4502

9. Physical and chemical properties ... / >>

Appearance	paste
Colour	black
Odour	characteristic
Odour threshold	Not available
pH	Not available
Melting point / freezing point	Not available
Initial boiling point	270 °C (518 °F)
Boiling range	Not available
Flash point	Not applicable
Evaporation rate	Not available
Flammability (solid, gas)	not flammable
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,21 - 1,23
Solubility	Not available
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	> 300 °C
Decomposition temperature	Not available
Viscosity	300000 - 400000 cps
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

Information not available

10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

Information not available

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effectsMetabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

4502

11. Toxicological information ... / >>

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

CARBON BLACK.

LD50 (Oral)

> 8000 mg/kg Rattus sp,

LD50 (Dermal)

> 3000 mg/kg Oryctolagus sp,

LC50 (Inhalation)

> 27 mg/l/1h Rattus sp,

DIPHENYLMETHANE-4,4'-DIISOCYANATE

LD50 (Oral)

> 2000 mg/kg Rattus sp,

LD50 (Dermal)

> 9400 mg/kg Oryctolagus sp,

LC50 (Inhalation)

1.5 mg/l/4h Rattus sp,

DIISONONYL PHTHALATE

LD50 (Oral)

> 10000 mg/kg Rat - Sprague-Dawley

LD50 (Dermal)

> 3160 mg/kg Rabbit - New Zeland white

LC50 (Inhalation)

> 4.4 mg/l Rat - Sprague-Dawley

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

Sensitising for the respiratory system

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Suspected of causing cancer

Carcinogenicity Assessment:

1333-86-4

CARBON BLACK.

IARC:2B

101-68-8

DIPHENYLMETHANE-4,4'-DIISOCYANATE

IARC:3

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

4502

Does not meet the classification criteria for this hazard class

12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

CARBON BLACK.

LC50 - for Fish > 1000 mg/l/96h Brachydanio rerio
EC50 - for Algae / Aquatic Plants > 10000 mg/l/72h Scenedesmus subspicatus

DIPHENYLMETHANE-4,4'-DIISOCYANATE

LC50 - for Fish > 1000 mg/l/96h Danio rerio
EC50 - for Algae / Aquatic Plants > 1640 mg/l/72h Scenedesmus subspicatus
Chronic NOEC for Crustacea > 10 mg/l Daphnia magna
Chronic NOEC for Algae / Aquatic Plants 1640 mg/l Desmodesmus subspicatus

DIISONONYL PHTHALATE

LC50 - for Fish > 102 mg/l/96h Danio rerio
EC50 - for Crustacea > 74 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants > 88 mg/l/72h Scenedesmus subspicatus

12.2. Persistence and degradability

DIISONONYL PHTHALATE

Solubility in water < 0.1 mg/l
Rapidly degradable

12.3. Bioaccumulative potential

DIISONONYL PHTHALATE

Partition coefficient: n-octanol/water 8.8
BCF > 3

12.4. Mobility in soil

DIISONONYL PHTHALATE

Partition coefficient: soil/water 6

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage \geq than 0,1%.

12.6. Other adverse effects

Information not available

4502

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal Regulations

TSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATE

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act – Priority Pollutants:

No component(s) listed.

15. Regulatory information ... / >>Clean Water Act – Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):

No component(s) listed.

EPA List of Lists:

313 Category Code:

101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATE

EPCRA 302 EHS TPQ:

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATE

EPCRA 313 TRI:

101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATE

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

No component(s) listed.

State RegulationsMassachusetts:1333-86-4 CARBON BLACK.
101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATEMinnesota:1333-86-4 CARBON BLACK.
101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATENew Jersey:1333-86-4 CARBON BLACK.
101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATENew York:

101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATE

Pennsylvania:1333-86-4 CARBON BLACK.
101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATECalifornia:1333-86-4 CARBON BLACK.
101-68-8 DIPHENYLMETHANE-4,4'-DIISOCYANATEProposition 65:

WARNING! This product contains chemicals known to the State of California to cause cancer and birth defects or reproductive harm.

1333-86-4 CARBON BLACK. C
28553-12-0 DIISONONYL PHTHALATE (Diisononyl phthalate (DINP))International RegulationsSubstances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H351	Suspected of causing cancer.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.

LEGEND:

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 3
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".

16. Other information ... / >>

- New Jersey Worker and Community Right to know Act N.J.S.A. - NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

03.